

How to update PGS servos firmware by Multi Setting Gear

Firmware update table

Servo Name	File Name	Display information After update	Multi Setting Gear
PGS-LH	P5101106	V51.01R106	○
PGS-XB	P5101207	V51.01R207	○
PGS-XR	P5101307	V51.01R307	○
PGS-LH Type-D	P5101403	V51.01R403	○
PGS-CL and CX	P5201103	V52.01R103	○

1. Insert Micro SD card to your computer

save unzip file (P5*****.PRO) to root in Micro SD card.

2. Insert Micro SD card to Multi Setting Gear

Connect PGS-CL or PGS-CX to Multi Setting Gear, then turning on the Gear.

3. If the Gear display "SERVO CONNECT OK?,"

press back key 3 times and display

"SETTING GEAR FOR PGS-LH/XB/XR or SETTING GEAR FOR PGS-CL/CX."

*If the display did not show the connected PGS servos,

it need to switch Multi Setting Gear Firmware for connected servos.

Please check how to change Multi Setting Gear firmware on our website.

(http://sanwa-denshi.com/rc/car/option2/multi_setting_gear.html)

4. Move to "SERVO PROGRAM UPDATE [3]" by ▲SELECT▼ key

Press Enter key.

5. Select update file "P5201103" by ▲SELECT▼ key

Press Enter to start update.

(Firmware update will be finished for
about 10 seconds after press enter.)

6. After update is completed, please move to "INFORMATION (VERSION)[4]"

Enter to check "PGS:V5*.01R.***."