






PGS2 Servos complete List

Product Name	PGS-LHI II	PGS-CLII	PGS-XBI II	PGS-XRI II	PGS-CX II
Picture					
Voltage	4.8 ~ 7.4V	4.8 ~ 7.4V	4.8 ~ 7.4V	4.8 ~ 7.4V	4.8 ~ 7.4V
Torque	15.6 kg/cm (7.4V) 12.8 kg/cm (6.0V)	16.6 kg/cm (7.4V) 14.7 kg/cm (6.0V)	21.1 kg/cm (7.4V) 17.9 kg/cm (6.0V)	17.3 kg/cm (7.4V) 14.0 kg/cm (6.0V)	31.0 kg/cm (7.4V) 25.1 kg/cm (6.0V)
Speed	0.09 sec/60°(7.4V) 0.11 sec/60° (6.0V)	0.08 sec/60°(7.4V) 0.11 sec/60° (6.0V)	0.11 sec/60°(7.4V) 0.14 sec/60° (6.0V)	0.09 sec/60°(7.4V) 0.11 sec/60° (6.0V)	0.11 sec/60°(7.4V) 0.13 sec/60° (6.0V)
Size	40.2 x 20.5 x 26.0 mm	40.5 x 20.5 x 26.5 mm	40.5 x 20.5 x 38.7 mm	40.5 x 20.5 x 38.7 mm	40.5 x 20.5 x 37.2 mm
Weight	53.0 g	49.6 g	72.0 g	72.0 g	62.0 g
Gears	Full Metal Gears	Metal Gears	Full Metal Gears	Full Metal Gears	Metal Gears
Case	Full Aluminium Case	Aluminium Heat Case	Full Aluminium Case	Full Aluminium Case	Aluminium Heat Case
CODE 10	Compatible	Compatible	Compatible	Compatible	Compatible
Waterproof	—	Same as IPX4	—	—	Same as IPX4
Information	—	AL bearing standard installation	—	—	AL bearing standard installation

* ALL PGS-II Servos are programmable servos, can be set by

MULTI-SETTING GEAR, SSL CODE10, and M17 Multi Setting Gear Function.

SSL10
EDGE-AUX
SUPERCHARGED LINK

